

# ATTACHMENTS

Equipped with additional tools, your Brokk machine turns into a multi-purpose, profit-generating marvel for your business. Grapples, drum cutters, buckets, drills and other devices greatly expand the machine's versatility and efficiency. Here's our wide and ever-expanding range of original Brokk attachments.



BHB 455



## BREAKERS

	Hitting power*	Blows/min	Weight	Made for
<b>BHB 55</b>	101 J/Nm	750 – 1 700	55 kg/121 lbs	Brokk 60
<b>BHB 105</b>	159 J/Nm	750 – 2 300	100 kg/221 lbs	Brokk 110, 120
<b>BHB 155</b>	254 J/Nm	850 – 1 900	140 kg/309 lbs	Brokk 110, 120, 170
<b>BHB 205</b>	406 J/Nm	850 – 1 800	205 kg/452 lbs	Brokk 170
<b>BHB 305</b>	610 J/Nm	600 – 1 400	295 kg/650 lbs	Brokk 200, 300
<b>BHB 455</b>	855 J/Nm	550 – 1 250	410 kg/904 lbs	Brokk 300, 800P
<b>BHB 555</b>	1 048 J/Nm	650 – 1 150	520 kg/1 146 lbs	Brokk 500, 520D
<b>BHB 705</b>	1 472 J/Nm	600 – 1 050	685 kg/1 510 lbs	Brokk 500, 520D
<b>MB 1200</b>	2 709 J/Nm	340 – 680	1 200 kg/2 646 lbs	Brokk 800S

\*Actual output, impact energy class (Joule/Nm)  
A variety of chisels and tools can be fitted to the breakers.



## CONCRETE CRUSHERS\*



CC580

	Jaw opening	Rebars	Crushing force	Weight	Made for
<b>CC260</b>	250 mm/9.8 in	Ø16 mm/0.6 in	220 kN/22 t/ 49 x 10 <sup>3</sup> lbf	82 kg/ 181 lbs	Brokk 60
<b>CC340</b>	343 mm/14 in	Ø30 mm/1.2 in	360 kN /37 t/ 81 x 10 <sup>3</sup> lbf	160 kg/ 353 lbs	Brokk 110, 120D
<b>CC440</b>	440 mm/17 in	Ø30 mm/1.2 in	430 kN /44 t/ 97 x 10 <sup>3</sup> lbf	265 kg/ 584 lbs	Brokk 170
<b>CC480</b>	460 mm/18 in	Ø30 mm/1.2 in	490 kN/50 t/ 110 x 10 <sup>3</sup> lbf	305 kg/ 672 lbs	Brokk 200
<b>CC580</b>	565 mm/22 in	Ø30 mm/1.2 in	530 kN/54 t/ 119 x 10 <sup>3</sup> lbf	430 kg/ 948 lbs	Brokk 300
<b>CC700</b>	650 mm/26 in	Ø30 mm/1.2 in	680 kN/70 t/ 153 x 10 <sup>3</sup> lbf	610 kg/ 1 345 lbs	Brokk 500, , 520D, 800S

\*Free rotation



## METAL SHEARS\*



	Cutting force	Opening width	Weight	Made for
<b>MC200</b>	490 kN/50 t/110 Klbf	200 mm/7.9 in	165 kg/364 lbs	Brokk 110, 120, 170
<b>TC120</b>	660 kN/60 t/149 Klbf	125 mm/4.9 in	305 kg/672 lbs	Brokk 200, 300
<b>CC420S</b>	740 kN/75 t/166 Klbf	145 mm/6 in	300 kg/661 lbs	Brokk 200, 300
<b>CC700S</b>	1 840 kN/188 t/414 Klbf	268 mm/11 in	695 kg/1 532 lbs	Brokk 500, 520D, 800
<b>BMS 100</b>	647 kN/66 t/145 Klbf	195 mm/7.7 in	380 kg/838 lbs	Brokk 200, 300
<b>BMS 140</b>	863 kN/88 t/194 Klbf	290 mm/11.4 in	645 kg/1 422 lbs	Brokk 500, 520D
<b>BMS 250-H</b>	1 353 kN/138 t/304 Klbf	375 mm/14.8 in	1 360 kg/2 998 lbs	Brokk 800S

All weights are relate operational tool (incl: mounting plate, hoses, oil etc)



250 l

## BUCKETS\*

Volume	Width	Weight	Made for
20 l/0.7 cu ft	330 mm/13 in	20 kg/44 lbs	Brokk 60
60 l/2.1 cu ft	520 mm/20.5 in	61 kg/134 lbs	Brokk 110, 120D
80 l/2.8 cu ft	690 mm/27.2 in	76 kg/168 lbs	Brokk 170
150 l/5.3 cu ft	800 mm/31.5 in	120 kg/265 lbs	Brokk 200
250 l/8.8 cu ft	930 mm/36.6 in	150 kg/331 lbs	Brokk 300, 500, 520D, 800P
700 l/24.7 cu ft	1 050 mm/41.3 in	650 kg/1 433 lbs	Brokk 800S

\*See load diagram for each Brokk machine



C02H

## CLAMSHELL BUCKETS\*

	Volume	Opening range	Width	Weight	Made for
<b>C01H-20</b>	10 l/0.4 cu ft	429 mm/16.9 in	207 mm/8.1 in	61 kg/135 lbs	Brokk 60
<b>C02H-25</b>	25 l/0.9 cu ft	725 mm/28.5 in	250 mm/9.8 in	110 kg/243 lbs	Brokk 110, 120D
<b>C03H-35</b>	65 l/2.3 cu ft	880 mm/34.6 in	350 mm/13.8 in	175 kg/386 lbs	Brokk 170
<b>C05H-40</b>	115 l/4.1 cu ft	1 090 mm/42.9 in	400 mm/15.7 in	210 kg/463 lbs	Brokk 200
<b>C05HPX-40</b>	115 l/4.1 cu ft	1 110 mm/43.7 in	400 mm/15.7 in	325 kg/717 lbs	Brokk 300
<b>C05HPX-60</b>	170 l/6.0 cu ft	1 110 mm/43.7 in	600 mm/23.6 in	390 kg/860 lbs	Brokk 500, 520D
<b>C08HPX-80</b>	300 l/10.6 cu ft	1 250 mm/49.2 in	800 mm/31.5 in	580 kg/1 279 lbs	Brokk 800S

\*See load diagram for each Brokk machine  
 Rotator with continuous rotation  
 Requires one extra hydraulic function  
 Only for material handling, not for demolition.





A06HPX-45



KM651-4



## MULTI PURPOSE GRAPPLES\*

	Volume	Opening range	Width	Weight	Made for
<b>A01H-20</b>	10 l/0.4 cu ft	429 mm/16.9 in	207 mm/8.1 in	61 kg/135 lbs	Brokk 60
<b>A02H-30</b>	35 l/1.2 cu ft	835 mm/32.9 in	300 mm/11.8 in	152 kg/335 lbs	Brokk 110, 120D, 170
<b>A04H-40</b>	70 l/2.5 cu ft	1 233 mm/48.5 in	386 mm/15.2 in	237 kg/522 lbs	Brokk 200
<b>A04HPX-40</b>	70 l/2.5 cu ft	1 050 mm/41.3 in	386 mm/15.2 in	325 kg/717 lbs	Brokk 300
<b>A06HPX-45</b>	145 l/5.1 cu ft	1 344 mm/52.9 in	450 mm/17.7 in	430 kg/948 lbs	Brokk 500, 520D
<b>A09HPX-50</b>	210 l/7.4 cu ft	1 550 mm/61.0 in	500 mm/19.7 in	640 kg/1 411 lbs	Brokk 800S
<b>Orange Peel Grapple</b>					
<b>KM651-4 180</b>	180 l/6.4 cu ft	1 450 mm/57.1 in	1 070 mm/42.1 in	520 kg/1 146 lbs	Brokk 500, 520D
<b>KM651-4 240</b>	240 l/8.5 cu ft	1 720 mm/67.7 in	1 125 mm/44.3 in	870 kg/1 918 lbs	Brokk 800S

\*See load diagram for each Brokk machine  
Requires one extra hydraulic function  
Rotator with continuous rotation



G30



D02H



## SORTING & DEMOLITION GRAPPLES\*

	Jaw opening	Weight	Made for
<b>G30</b>	300 mm/11.8 in	42 kg/93 lbs	Brokk 60
<b>G50</b>	400 mm/15.7 in	140 kg/309 lbs	Brokk 110, 120D, 170
<b>D02H-30</b>	790 mm/31.1 in	133 kg/293 lbs	Brokk 110, 120D, 170
<b>D04H-40</b>	1 239 mm/48.8 in	232 kg/511 lbs	Brokk 200
<b>D04HPX-40</b>	1 051 mm/41.4 in	335 kg/739 lbs	Brokk 300
<b>D06HPX-45</b>	1 350 mm/53.1 in	435 kg/959 lbs	Brokk 500, 520D
<b>D09HPX-50</b>	1 550 mm/61.0 in	645 kg/1 422 lbs	Brokk 800S

\*See load diagram for each Brokk machine  
Requires one extra hydraulic function  
Rotator with continuous rotation

All weights are relate operational tool (incl: mounting plate, hoses, oil etc)



BCP250



## PLANERS

	Cutting depth	Width	Weight	Made for
<b>BCP 215* **</b>	0-5 mm/0-0.2 in	265 mm/10.4 in	265 kg/584 lbs	Brokk 110, 120D
<b>BCP 250* **</b>	0-5 mm/0-0.2 in	265 mm/10.4 in	345 kg/761 lbs	Brokk 200
<b>BCP 350* **</b>	0-5 mm/0-0.2 in	335 mm/13.2 in	600 kg/1 323 lbs	Brokk 300, 500, 520D
<b>EX20HD* ***</b>	0-70 mm/0-2.8 in	200 mm/7.9 in	210 kg/463 lbs	Brokk 170, 200
<b>EX30HD* ***</b>	0-120 mm/0-4.7 in	300 mm/11.8 in	460 kg/1 014 lbs	Brokk 300, 500, 520D

\*Available with cover and suction

\*\*Requires extra hydraulic function, drainage hose, cable kit, counter weight in some occasions  
Requires load holding. On request

\*\*\*Requires drainage hose

TE 160-100



## DRILLING EQUIPMENT\*\*\*

	Length	Drill diameters	Drill steel size	Max. stroke length**	Weight	Made for
<b>TE 160-100</b>	1 910 mm/ 75.2 in	33 – 42mm 1.3 – 1.7 in	R25	1 000 mm/ 3.3 ft	225 kg/ 496 lbs	Brokk 110, 120, 170
<b>TE 260-180*</b>	2 900 mm/ 114.2 in	33 – 52 mm 1.3 – 2 in	R32	1 830 mm/ 6 ft	415 kg/ 915 lbs	Brokk 200, 300, 500, 520D
<b>TE 260-240*</b>	3 500 mm/ 137.8 in	33 – 52 mm 1.3 – 2 in	R32	2 435 mm/ 8 ft	432 kg/ 952 lbs	Brokk 300, 500, 520D
<b>TE 326-180*</b>	3 200 mm/ 126.2 in	42 – 76 mm 1.7 – 3 in	R32	1 830 mm/ 6 ft	440 kg/ 960 lbs	Brokk 300, 500, 520D
<b>TE 326-240*</b>	3 800 mm/ 149.8 in	42 – 76 mm 1.7 – 3 in	R32	2 435 mm/ 8 ft	450 kg/ 992 lbs	Brokk 300, 500, 520D
<b>TE 360-240*</b>	3 590 mm/ 141.3 in	42 – 76 mm 1.7 – 3 in	R32	2 435 mm/ 8 ft	644 kg/ 1 420 lbs	Brokk 500, 520D, 800S

\*Extension rod drilling on request

\*\*Per stroke with open centralizer

\*\*\*Requires drainage hose, cable kit, counterweight in some occasions, water or airflushing

All weights are relate operational tool (incl: mounting plate, hoses, oil etc)

BDC 100



## ■ DRUM CUTTERS

	Cutting depth**	Width	Weight	Made for
<b>RT 15-40*</b>	0-5 mm/0-0.2 in	120 mm/4.7 in	66 kg/146 lbs	Brokk 60
<b>BDC 50***</b>	0-30 mm/0-1.2 in	480 mm/18.9 in	160 kg/353 lbs	Brokk 110, 120, 170
<b>BDC 100***</b>	0-65 mm/0-2.6 in	610 mm/24 in	345 kg/761 lbs	Brokk 200, 300, 500, 520D, 800P
<b>BDC 250***</b>	0-80 mm/0-3.1 in	680 mm/26.8 in	545 kg/1 202 lbs	Brokk 500, 520D, 800S

\*Cover and suction on request

\*\*Data depending on concrete quality

\*\*\*Requires drainage hose

Brokk Beam Grapple



## ■ BEAM GRAPPLE\*

	Jaw opening	Beam weight	Weight	Made for
<b>Brokk Beam Grapple</b>	250 mm/9.8 in	B300: 150 kg/331 lbs B500: 500 kg/1 102 lbs B800: 500 kg/1 102 lbs	320 kg/705 lbs	Brokk 300, 500, 520D, 800S

\*Requires load holding valves with hose burst function  
Requires two extra hydraulic functions

Brokk Shot Crete



## ■ SHOT CRETE\*

	Concrete hose (di)	Gunning pressure	Air pressure	Weight	Made for
<b>Brokk Shot Crete</b>	45 mm/ 1.8 in	Depend on concrete pump	Depend on concrete pump	180 kg/397 lbs	Brokk 200, 300, 500, 520D, 800S

\*Requires two extra hydraulic functions

All weights are relate operational tool (incl: mounting plate, hoses, oil etc)

BCS10



## CUT OFF SAW\*

	Saw disk diameter**	Cutting depth***	Weight	Made for
<b>BCS 8</b>	400 mm/16 in	170 mm/7 in	62 kg/137 lbs	Brokk 60
<b>BCS 10</b>	400 mm/16 in	170 mm/7 in	65 kg/143 lbs	Brokk 110, 120, 170
<b>BCS 25****</b>	800 mm/31 in	260 mm/10 in	192 kg/423 lbs	Brokk 170
<b>BCS 35****</b>	800 mm/31 in	260 mm/10 in	195 kg/430 lbs	Brokk 200, 300, 500, 520D, 800S

\*Requires one extra hydraulic function

\*\*Different saw disks available depending on material

\*\*\*With new saw disk

\*\*\*\*Requires drainage hose

C20 J



## SPLITTERS

	Length	Drill hole diameter	Splitting force theoretical	Weight	Made for
<b>C20 V**</b>	1 833 mm/72 in	76 mm/3 in	14 760 kN-17 660 kN/ 1 500 t-1 800 t	455 kg/ 1 003 lbs	Brokk 300*, 500, 520D
<b>C20 H***</b>	1 790 mm/70 in	76 mm/3 in	14 760 kN-17 660 kN/ 1 500 t-1 800 t	460 kg/ 1 014 lbs	Brokk 300*, 500, 520D
<b>C20 J**</b>	2 110 mm/83 in	76 mm/3 in	14 760 kN-17 660 kN/ 1 500 t-1 800 t	440 kg/ 970 lbs	Brokk 300*, 500, 520D

\*Require counterweight

\*\*Requires one extra hydraulic function

\*\*\*Requires two extra hydraulic functions

PTA-09



## SIDE ANGLING DEVICE\*\*

	Angle	Weight*	Made for
<b>PTA-04,5</b>	±60°	140 kg/309 lbs	BHB 105/Brokk 110, 120D
<b>PTA-06</b>	±70°	215 kg/474 lbs	BHB 155/Brokk 170
<b>PTA-07</b>	±67°	330 kg/728 lbs	BHB 205/Brokk 200, 300
<b>PTA-09</b>	±53°	555 kg/1 224 lbs	BHB 305/Brokk 500, 520D

\*With breaker

\*\*Requires one extra hydraulic function

All weights are relate operational tool (incl: mounting plate, hoses, oil etc)